

PORT KING PLUS - Teknik Özellikler



Description

PORT KING PLUS intermodal taşımacılık/lojistik uygulamalarında kullanılan dolu konteyner mobil vinçleri için özel olarak tasarlanmıştır. Özel bileşiği ve dayanıklı çekmelere sahip derin diş deseni, daha uzun bir lastik ömrü sunar. Oluk Çatlamasına Karşı Dayanıklı Diş Bileşiği (GCRC) ile birlikte de sunulmaktadır.

UM

International Standard

Construction

BIAS

Machinery

Endüstriyel: Konteyner yükleyici

Version	GCRC
Type	TL
Tyre Size	18.00 - 25

Dimensions International Standard

Ply Rating	40
Overall Width (mm)	528
Overall Diameter (mm)	1675
Static Loaded Radius (mm)	765
Rolling Circumference (mm)	4955
Rim Rec	13.00 /2.5
Rim Alt	15.00/2.5
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	22950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16.05.2025 22:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..