

RIB F3 - Teknik Özellikler



Description

RIB F3, toprak işleme ve taşıma operasyonlarında kullanılan tek çeker traktörler için tasarlanmış, araziye yönelik bir lastiktir. Bazı ebatlar römork kullanılan taşıma uygulamaları için uygundur. RIB F3 lastik, yüksek seviye elleçleme gerektiren tüm operasyonlar için ideal bir ortaktır. Mükemmel dayanıklılık ve anız direnci sağlamak için sert bir hamur ile tasarlanmıştır.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Tek çeker traktör • Römork

Version	STANDARD
Type	TL
Tyre Size	9.00 - 16
LI/SS	120 A6/ 112 A8

Dimensions US Standard

Usa code	94060016
Ply Rating	12
Section Width (inch)	9.6
Overall Diameter (inch)	34.6
Static Loaded Radius (inch)	15.2
Rolling Circumference (inch)	101.3
Rim Rec	W 8
Rim Alt	6.00 F ; W 7 ; W 8 L
ECE	E11-106R-004592
TRA Code	F3

Load capacity (lbs)

mph / psi	68
20	3090
25	2470

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16/05/2025 22:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..