

# RM 2002 - Teknik Özellikler



## Description

RM 2002 hem yolda hem de arazide, römorklar ve hafif kamyonlarla yapılan taşımacılık faaliyetleri için uygundur. Ürün ömür döngüsü boyunca, uzun süreli dayanıklılık ve yüksek performans sağlar. "Endüstriyel" modeli kaldırma ve taşıma tipi vinçler için idealdır.

#### UM

US Standard

#### Construction

🐼 BIAS

### Machinery

Zirai: Römork Endüstriyel: Mobil Vinç

Version	INDUSTRIAL
Туре	Π
Tyre Size	11.00 - 20

## **Dimensions US Standard**

Usa code	94027200
Ply Rating	16
Section Width (inch)	11.9
Overall Diameter (inch)	43.3
Rim Rec	8.0
Rim Alt	7.5 ; 8.5

# Load capacity (lbs)

mph / psi	115	105
62 LS	7165	-
62 LD	-	6395

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 16.05.2025 22:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..