

SKID POWER - Teknik Özellikler



Description

SKID POWER inşaat uygulamalarında kullanılan nokta dönüşlü yükleyiciler için tasarlanmıştır. Sıra dışı kendini temizleme özelliklerinin yanı sıra, kusursuz çekiş gücüne sahiptir. Lastik, ekstra derin desene ve kesilme ve parçalanmaya karşı yüksek dayanıklılık ve olağanüstü sağlamlık sağlayan yanak korumasına sahiptir. SKID POWER gevşek yüzeyler için ideal lastiktir.

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Mini yükleyici

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	254
Overall Diameter (mm)	775
Static Loaded Radius (mm)	355
Rolling Circumference (mm)	2286
Rim Rec	8.25

Load capacity (Kg)

km/h / bar	5.20
10	2135
15	1685
25	1560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 02:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..