

## SM 55 L5S - Veri Sayfasını İndir



### Description

SM 55 (L-5S) yeraltı madenciliği çalışmaları için ideal, çapraz kuşaklı bir lastiktir. Özel tasarımı, kesilme ve parçalanmaya karşı dayanıklı diş bileşiği delinmeleri en aza indirerek makine çalışmama süresini azaltır. Ekstra derin L-5 diş derinliği daha uzun lastik ömrünü garanti eder. Lastiğin çelik kuşaklı bir modeli de bulunmaktadır.

### UM

US Standard

### Construction

BIAS

### Machinery

Yoldışı: Düşük profilli damperli kamyon • Yeraltı madenciliği aracı

| SIZE       | Version      | USACode  | TRA Code | PR | RIM REC   | RIM ALT                      | OW   | OD    | SLR  | RC    | Type | Tread Depth |
|------------|--------------|----------|----------|----|-----------|------------------------------|------|-------|------|-------|------|-------------|
| 7.00 - 12  | DUAL BEAD    | 94058716 | L5S      | 16 | 5.00 S    |                              | 8.1  | 28    | 12.7 | 85    | TT   | 39          |
| 7.00 - 12  | STANDARD     | 94044986 | L5S      | 14 | 5.00 S    |                              | 8.1  | 28    | 12.7 | 85    | TT   | 39          |
| 7.00 - 12  | STANDARD     | 94046058 | L5S      | 16 | 5.00 S    |                              | 8.1  | 28    | 12.7 | 85    | TT   | 39          |
| 9.50 - 20  | STANDARD     | 94061853 | L5S      | 16 | 7.5       |                              | 10.8 | 41.9  | 19.9 | 129.1 | TT   | 72          |
| 12.00 - 24 | STANDARD     | 94030873 | L5S      | 20 | 8.5       | 7.33 V ; 8 ; 8.00 V ; 8.50 V | 12.2 | 50.2  | 23.4 | 148.7 | TT   | 76          |
| 12.00 - 24 | STANDARD     | 94030835 | L5S      | 24 | 8.5       | 7.33 V ; 8 ; 8.00 V ; 8.50 V | 12.2 | 50.2  | 23.4 | 148.7 | TT   | 76          |
| 12.00 - 24 | STEEL BELTED | 94035984 | L5S      | 24 | 8.5       | 7.33 V ; 8 ; 8.00 V ; 8.50 V | 12.2 | 50.2  | 23.4 | 148.7 | TT   | 76          |
| 17.5 - 25  | ARASHIELD    | 94052974 | L5S      | 24 | 14.00/1.5 | 14.00/1.3 ; 14.00/1.4 (DC)   | 17.2 | 54.1  | 24.8 | 159.2 | TL   | 80          |
| 17.5 - 25  | STANDARD     | 94030651 | L5S      | 24 | 14.00/1.5 | 14.00/1.3 ; 14.00/1.4 (DC)   | 17.2 | 54.1  | 24.8 | 159.2 | TL   | 80          |
| 17.5 - 25  | STANDARD     | 94025886 | L5S      | 20 | 14.00/1.5 | 14.00/1.3 ; 14.00/1.4 (DC)   | 17.2 | 54.1  | 24.8 | 159.2 | TL   | 80          |
| 17.5 - 25  | STEEL BELTED | 94040216 | L5S      | 20 | 14.00/1.5 | 14.00/1.3 ; 14.00/1.4 (DC)   | 17.2 | 54.1  | 24.8 | 159.2 | TL   | 80          |
| 17.5 - 25  | STEEL BELTED | 94040568 | L5S      | 24 | 14.00/1.5 | 14.00/1.3 ; 14.00/1.4 (DC)   | 17.2 | 54.1  | 24.8 | 159.2 | TL   | 80          |
| 18.00 - 25 | ARASHIELD    | 94052981 | L5S      | 40 | 13.00/2.5 | 15.00/2.5                    | 20.4 | 65.6  | 30.1 | 201.5 | TL   | 105         |
| 18.00 - 25 | STANDARD     | 94026807 | L5S      | 28 | 13.00/2.5 | 15.00/2.5                    | 20.4 | 65.6  | 30.1 | 201.5 | TL   | 105         |
| 18.00 - 25 | STANDARD     | 94025718 | L5S      | 40 | 13.00/2.5 | 15.00/2.5                    | 20.4 | 65.6  | 30.1 | 201.5 | TL   | 105         |
| 18.00 - 25 | STANDARD     | 94053230 | L5S      | 32 | 13.00/2.5 | 15.00/2.5                    | 20.4 | 65.6  | 30.1 | 201.5 | TL   | 105         |
| 18.00 - 25 | STEEL BELTED | 94040223 | L5S      | 28 | 13.00/2.5 | 15.00/2.5                    | 20.4 | 65.6  | 30.1 | 201.5 | TL   | 105         |
| 18.00 - 25 | STEEL BELTED | 94044696 | L5S      | 40 | 13.00/2.5 | 15.00/2.5                    | 20.4 | 65.6  | 30.1 | 201.5 | TL   | 105         |
| 20.5 - 25  | STANDARD     | 94069859 | L5S      | 20 | 17.00/2.0 |                              | 20.9 | 61.6  | 0    | 0     | TL   | 101         |
| 26.5 - 25  | ARASHIELD    | 94052998 | L5S      | 36 | 22.00/3.0 |                              | 27.6 | 70.8  | 32.1 | 209.5 | TL   | 121         |
| 26.5 - 25  | STEEL BELTED | 94039951 | L5S      | 28 | 22.00/3.0 |                              | 27.6 | 70.8  | 32.1 | 209.5 | TL   | 121         |
| 26.5 - 25  | STEEL BELTED | 94045488 | L5S      | 32 | 22.00/3.0 |                              | 27.6 | 70.8  | 32.1 | 209.5 | TL   | 121         |
| 29.5 - 29  | ARASHIELD    | 94064267 | L5S      | 40 | 25.00/3.5 | 24.00/3.5                    | 29.7 | 79.5  | 34.7 | 237   | TL   | 131         |
| 29.5 - 29  | STEEL BELTED | 94058242 | L5S      | 40 | 25.00/3.5 | 24.00/3.5                    | 29.7 | 79.5  | 34.7 | 237   | TL   | 131         |
| 29.5 - 29  | STEEL BELTED | 94040407 | L5S      | 28 | 25.00/3.5 | 24.00/3.5                    | 29.7 | 79.5  | 34.7 | 237   | TL   | 131         |
| 35/65 - 33 | ARASHIELD    | 94063864 | L5S      | 48 | 28.00/3.5 |                              | 36.2 | 82.1  | 0    | 0     | TL   | 123         |
| 35/65 - 33 | STEEL BELTED | 94060931 | L5S      | 48 | 28.00/3.5 |                              | 36.2 | 82.1  | 0    | 0     | TL   | 123         |
| 45/65 - 45 | STEEL BELTED | 94058730 | L5S      | 58 | 36.00/4.5 |                              | 45.1 | 108.3 | 0    | 0     | TL   | 146         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18.05.2025 03:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..