

TR 137 - Teknik Özellikler



Description

TR 137, BKT'nin, tüm hasat operasyonlarına en uygun lastiğidir. Yüksek yüklerde bile tarlalarda mükemmel çekiş sağlar. Lastik farklı versiyonlarda sunulmaktadır: "aramid kuşaklı" versiyon daha iyi delinme direnci ve bu uygulamanın tüm tipik hasarlarına karşı koruma sağlar; "HD" versiyonu olağanüstü kesilme ve kopma direnci ve daha uzun lastik ömrü sunar.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Biçerdöver

Version	STANDARD
Type	TL
Tyre Size	24.5 - 32
LI/SS	163 A6

Dimensions International Standard

Ply Rating	14
Section Width (mm)	622
Overall Diameter (mm)	1805
Static Loaded Radius (mm)	807
Rolling Circumference (mm)	5343
SRI (mm)	825
Rim Rec	DW 21 B
Rim Alt	DW 20 B
ECE	E4-106R-002273
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.00
30	4875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/17/2025 3:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..