

## TR 137 - Teknik Özellikler



### Description

TR 137, BKT'nin, tüm hasat operasyonlarına en uygun lastiğidir. Yüksek yüklerde bile tarlalarda mükemmel çekiş sağlar. Lastik farklı versiyonlarda sunulmaktadır: "aramid kuşaklı" versiyon daha iyi delinme direnci ve bu uygulamanın tüm tipik hasarlarına karşı koruma sağlar; "HD" versiyonu olağanüstü kesilme ve kopma direnci ve daha uzun lastik ömrü sunar.

### UM

US Standard

### Construction

BIAS

### Machinery

Zirai: Biçerdöver

|           |            |
|-----------|------------|
| Version   | HD         |
| Type      | TL         |
| Tyre Size | 30.5L - 32 |
| LI/SS     | 167 A8     |

## Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94004355       |
| Ply Rating                   | 18             |
| Section Width (inch)         | 30.3           |
| Overall Diameter (inch)      | 73.4           |
| Static Loaded Radius (inch)  | 32.7           |
| Rolling Circumference (inch) | 217.3          |
| Rim Rec                      | DH 27 B        |
| Rim Alt                      | DW 27 B        |
| ECE                          | E4-106R-002283 |
| TRA Code                     | R1             |

## Load capacity (lbs)

|           |       |
|-----------|-------|
| mph / psi | 30    |
| 25        | 12010 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 03:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..