

## TR 171 - Teknik Özellikler



### Description

TR 171, toprak işleme operasyonlarında kullanılan traktörler uygun, derin sırtlı bir lastiktir. Olağanüstü kendi kendini temizleme özellikleri sayesinde ıslak ve nemli topraklar için idealdir. Özel bir hamurla tasarlanan TR 171, en zorlu çalışma koşullarında bile mükemmel çekiş ve olağanüstü dayanıklılık sağlar.

### UM

International Standard

### Construction

✚ BIAS

### Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	9.5 - 20
LI/SS	107 A6

# Dimensions International Standard

Ply Rating	8
Section Width (mm)	241
Overall Diameter (mm)	955
Static Loaded Radius (mm)	449
Rolling Circumference (mm)	2942
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-004105
TRA Code	R1W+

## Load capacity (Kg)

km/h / bar	2.80
30	975

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 04:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..