

TR 270 - Teknik Özellikler



Description

TR 270 toprak işleme uygulamaları için uygun bir traktör lastiğidir. Islak ve nemli toprakta maksimum performans sunmak için özel olarak tasarlanmıştır. Bu toprak koşullarında, bir lastiğin üstün tutuş ve gelişmiş kendini temizleme özellikleri sunması gereklidir. TR 270 bu nitelikleri eksiksiz şekilde karşılar.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	23.1 - 30
LI/SS	155 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	590
Overall Diameter (mm)	1748
Static Loaded Radius (mm)	790
Rolling Circumference (mm)	5227
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-004504
TRA Code	R2

Load capacity (Kg)

km/h / bar	1.70
30	3875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 03:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..