

## AW 705 - Technical Specifications



### Description

AW 705 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. It is ideal for modern farming thanks to improved durability and high load capacity.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TT
Tyre Size	14.0/65 - 16
LI/SS FREE ROLLING	134 A8

## Dimensions US Standard

Usa code	94009909
Ply Rating	10
Section Width (inch)	13.9
Overall Diameter (inch)	34.3
Static Loaded Radius (inch)	15.3
Rolling Circumference (inch)	100.4
Rim Rec	11.0

## Load capacity (lbs)

mph / psi	41
5 FR	6550
15 FR	5370
20 FR	5240
25 FR	4670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/17/2025 6:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..