



XL GRIP (E3) - Data Sheet



Description

XL GRIP (E-3) is a bias-ply tire for rigid dump trucks designed to minimize cuts and punctures in severe conditions where exceptional traction is required. These features result in an extended tire life.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Rigid Dump Truck

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
16.00 - 25	STANDARD	94015689	E3/L3	28	11.25/2.0	13.00/2.0	18.3	58.5	26.9	173	TL	37
16.00 - 25	STANDARD	94015696	E3/L3	32	11.25/2.0	13.00/2.0	18.3	58.5	26.9	173	TL	37
18.00 - 25	STANDARD	94015757	E3/L3	24	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TT	40
18.00 - 25	STANDARD	94015764	E3/L3	32	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TT	40
18.00 - 25	STANDARD	94015771	E3/L3	32	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TL	40
18.00 - 25	STANDARD	94025817	E3/L3	40	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TT	40
18.00 - 25	STANDARD	94015788	E3/L3	40	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TL	40
18.00 - 25	STANDARD	94043347	E3/L3	16	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TL	40
18.00 - 33	STANDARD	94015795	E3	32	13.00/2.5		20.1	71.7	33.1	212	TT	40
18.00 - 33	STANDARD	94015801	E3	32	13.00/2.5		20.1	71.7	33.1	212	TL	40
18.00 - 33	STANDARD	94015818	E3	36	13.00/2.5		20.1	71.7	33.1	212	TL	40
18.00 - 33	STANDARD	94015825	E3	40	13.00/2.5		20.1	71.7	33.1	212	TL	40

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 00:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..