

XL GRIP (G3) - Technical Specifications



Description

XL GRIP (G-3) is a bias-ply tire for graders designed to minimize cuts and punctures in heavy-duty grading environments where exceptional traction is required.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Grader

Version	STANDARD
Type	TL
Tyre Size	16.00 - 24 (-)

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	432
Overall Diameter (mm)	1450
Static Loaded Radius (mm)	654
Rolling Circumference (mm)	4289
SRI (mm)	-
Rim Rec	10.00 VA SDC
Rim Alt	-
TRA Code	G3
Tread Depth	32

Load capacity (Kg)

km/h / bar	3.00
40	4500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 22:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..